Model Number **260A13**	**FORCE SENSOR, CHARGE OUTPUT, 3-COMPONENT**	Revision N ECN #: 23150

Performance	**ENGLISH**	**SI**	
Sensitivity (±15 %) (z axis)	15 pC/lb	3.37 pC/N	[2]
Sensitivity (±15 %) (x or y axis)	32 pC/lb	7.19 pC/N	[2]
Measurement Range (z axis)	10000 lb	44.48 kN	
Measurement Range (x or y axis)	4000 lb	17.7 kN	
Maximum Force (z axis)	11000 lb	48.93 kN	
Maximum Force (x or y axis)	4400 lb	19.57 kN	
Maximum Moment (z axis)	240 ft-lb	325.4 Nm	
Maximum Moment (x or y axis)	325 ft-lb	440.7 Nm	
Upper Frequency Limit	39 kHz	39 kHz	
Non-Linearity	≤1 % FS	≤1 % FS	[3]
Cross Talk (between x and y axis)	±3 %	±3 %	
Cross Talk (between (x or y axis) and z axis)	±5 %	±5 %	
Environmental			
Temperature Range	-100 to +350 °F	-73 to +177 °C	
Electrical			
Capacitance (all channels)	70 pF	70 pF	[1]
Insulation Resistance (all channels)	$\geq 10^{12}$ Ohm	$\geq 10^{12}$ Ohm	
Output Polarity (in direction of markings)	Negative	Negative	
Physical			
Preload	≤40000 lb	≤178 kN	[4]
Stiffness (z axis)	40 lb/µin	7 kN/µm	[1]
Stiffness (x or y axis)	15 lb/µin	2.6 kN/µm	[1]
Size (Height x Length x Width x Bolt Diameter x ID x Sensing Surface)	0.790 in x 2.25 in x 2.25 in x 1 in x 1.023 in x 1.800 in	20.07 mm x 57.1 mm x 57.1 mm x 25 mm x 25.98 mm x 45.72 mm	
Weight	9.88 oz	280 gm	
Housing Material	Stainless Steel	Stainless Steel	
Sealing	Hermetic	Hermetic	
Electrical Connector (Quantity, 3)	10-32 Coaxial Jack	10-32 Coaxial Jack	
Electrical Connection Position	Side	Side	

Optional Versions (Optional versions have identical specifications and accessories as listed for standard model except where noted below. More than one option maybe used.)

M - Metric Mount
Supplied Accessory: Model M081A71 Mounting Stud replaces Model 081A71

W - Water Resistant Cable

Electrical Connection Position	Side	Side

Notes

[1] Typical.
[2] Sensitivites are for listed preload. Sensitivites may vary ±5% depending on preload used.
[3] Zero-based, least-squares, straight line method.
[4] Preload should be at least 10 times the X and Y operating range used.

Supplied Accessories

081A71 Mounting Stud (1)
082B06 Anti-Friction Washer (1)
083A11 Pilot Bushing (1)

Entered: BLS	Engineer: MJK	Sales: JJM	Approved: BLS	Spec Number:
Date: 11/07/2005	Date: 11/09/2005	Date: 11/10/2005	Date: 11/10/2005	**6231**

All specifications are at room temperature unless otherwise specified.
In the interest of constant product improvement, we reserve the right to change specifications without notice.
ICP® is a registered trademark of PCB group, Inc.

PCB PIEZOTRONICS
FORCE / TORQUE DIVISION

3425 Walden Avenue
Depew, NY 14043
UNITED STATES
Phone: 800-828-8840
Fax: 716-684-0987
E-mail: info@pcb.com
Web site: www.pcb.com